

# Sinkware Installation Guide

Thank you for choosing Sergio Sinkware

## Important

All sinks should be installed by a skilled and experienced sink installer.

## Clipping

- Clips should be tightened by hand as often clips are blamed when the installer loses control with a powered screw driver.
- Clips will not withstand endless or uncontrollable tightening.

## Top Mounting

- When top mounting the sink ensure the edge that is in contact with the bench top surface is adequately sealed with silicone or a similar product to resist moisture damage.
- Always double-check that the cut out is 10-15mm smaller than the outside edge of the sink insert.
- Always allow the recommended time for the adhesive/sealant to cure before using your newly installed sink.

## Under Mounting

Under mounting requires specialist installation.

## Cut Out

- We recommend you have this sink insert on site when cutting out.
- We recommend that the raw edge of the cutout is sealed with a suitable sealant so there is no way it can absorb moisture.

## Care & Maintenance

Maintain the brilliance of your Sergio Sinkware!

- The Sergio product you have chosen is designed to provide many years of reliable service. However the finish on all sinkware requires care to retain its life.
- The everyday cleaning procedure is as follows:
  1. Rinse off all traces of soap thoroughly with clean water.
  2. Wipe dry and gently buff with a soft cloth.**Do not** use abrasive cleaners.